



32 Ft
390 Ft



INDUSTRIAL GRADE


CONNECTIONS

- Discharge: 1-1/2"
- Inlet: 2"
- Vent: 1-1/2"
- Fail proof air pressure switch system with triple redundancy.
- External control panel

PRODUCT FEATURES

- A duplex drain pump used for a variety of fixtures in commercial and industrial applications.
- Able to discharge the waste up to 32 feet vertical and/or 390 feet horizontal.
- Capable of handling up to 194° F water and grease.

PUMP CURVE



OPTIONAL ACCESSORIES

Descaler
(Part N° 052)
See page 28



Wired alarm unit



TECHNICAL SPECIFICATIONS

- Pump type:** Duplex drain pump
- Electrical:** 220-240 V (208V min) - 60 Hz / 16 Amps (Max)
- Motor:** 2 x 2 HP oil-filled thermally protected motor
- Capacitor rating:** 2 x 30 microfarad
- Operating Temperature:** 194°F
- Power cord length:** 72 inches
- Noise level:** ≤ 68 dBA (Lp) (measured at 3 ft.)
- Discharge pipe diameter:** 1-1/2"
- Discharge rate at 32 ft:** 81 GPM (Both motors in operation)
- Discharge rate at 3 ft:** 140 GPM (Both motors in operation)
- Shut-off head:** 53 ft.
- Normal running time:** Depends on number of fixtures
- Capacity:** 8.5 gallons / 32 liters
- Inlets:** 2" (sides), 1-1/2" vent (top)
- Method of activation:** Pressure switches, Circuit board
- Shower/bathtub base height:** 10" min
- Weight:** 57 lbs / 35 kg
- Certifying agencies:** CSA (IPC, NSPC), IAPMO (UPC)
- Recommended accessories:** Descaler
- Connections:** Commercial sinks, dishwasher, washing machine, etc.

DIMENSIONAL DRAWINGS

