


CONNECTIONS

- Discharge: 2"
- Vent: 2"
- Fail-proof air pressure switch system with triple redundancy.

PRODUCT FEATURES

- Pre-assembled retrofit pump kit with built-in 1 HP grinder and air pressure switches that adapts to 24" diameter basins.
- Able to discharge the waste up to 25 feet vertical and/or 328 feet horizontal.
- Easy access to all major internal components, including motor, grinder blade, and pressure switches.

PUMP CURVE



TECHNICAL SPECIFICATIONS

- Pump type:** Grinder
- Electrical:** 120 V - 60 Hz / 10 Amps (Max)
- Motor:** 1 HP oil-filled thermally protected motor
- Capacitor rating:** 60 microfarad
- Operating Temperature:** 158°F
- Power cord length:** 72 inches
- Noise level:** ≤ 68 dBA (Lp) (measured at 3 ft.)
- Discharge pipe diameter:** 2"
- Discharge rate at 25 ft:** 29 GPM
- Discharge rate at 3 ft:** 66 GPM
- Shut-off head:** 33 ft.
- Normal running time:** Depends on number of fixtures
- Basin Capacity:** 21 gallons / 80 liters
- Inlets:** 2" vent (top)
- Method of activation:** Pressure switches, Circuit board
- ON/OFF Levels:** 7-3/4" / 3-1/4"
- Weight:** 44 lbs / 20 kg
- Certifying agencies:** CSA (IPC, NSPC)

STANDARD ACCESSORIES



OPTIONAL



DIMENSIONAL DRAWINGS

